





轴承结构：滚珠轴承
Bearing System: Ball
外框材质：环保防火PBT UL94V-0
Frame: Thermoplastic PBT UL94V-0
扇叶材质：环保防火PBT UL94V-0
Impeller: Thermoplastic UL94V-0

尺寸图Dimension Drawing (Unit : mm)

P-Q 曲线图/P-Q Curve Chart



可选功能列表 Available Functions



配套产品选项 Attachment Option



型号 Model	额定电压 Rated Voltage	运行电压 Operation Voltage	额定电流 Rated Current	额定转速 Rated Speed	最大风量 Max. Air Flow		最大风压 Max. Air Pressure		噪音 Noise	重量 Weight
	VDC	VDC	A	RPM	CFM	m³/h	mmH₂O	Pa	dB(A)	g
XDB9733B12L	12	7.0~13.5	0.60	3500	22.06	37.48	17.54	171.89	49	164
XD9733B12M			1.00	4000	24.94	42.37	25.24	247.35	52	
XD9733B12H			4.00	4500	28.19	47.89	34.14	334.57	55	
XD9733B24L	24	18.0~26.4	0.30	3500	22.06	37.48	17.54	171.89	49	
XD9733B24M			0.50	4000	24.94	42.37	25.24	247.35	52	
XD9733B24H			0.80	4500	28.19	47.89	34.14	334.57	55	

注：以上数据仅供参考，如有变更恕不另行通知。

Notes: Above specification is only for reference and subject to change without notice.

AC Axial fan
AC轴流风机

EC Axial fan
EC轴流风机

DC fan
DC风机

AC Centrifugal fan
AC离心风机

EC Centrifugal fan
EC离心风机

AC External rotor fan
AC外转子风机

Fan filter
风扇过滤器

Governor/Voltage Regulator
调速器及调压器

Temperature control products
温控产品

Accessories
附件